



TRANSPORTATION SPECS - Boom Trucks

NATIONAL MODEL 15127 - 36 TON CAPACITY

COMPONENT WEIGHTS

| | <u>LBS.</u> | <u>KGS.</u> |
|---|-------------|-------------|
| Complete Crane & Truck (2005 Peterbuilt Model 357) | 51,880 | 23 587 |
| Crane Only | 32,201 | 14 606 |

ADDITIONAL INFORMATION

| | | |
|--|-------|-----|
| 31' Swingaway | 1,090 | 495 |
| 15 Ton Block (1 sheave) | 375 | 170 |
| 25 Ton Block (2 sheave) | 640 | 290 |
| Load Line 5/8" x 375' | 270 | 123 |
| Tire Size: Front: 425/65R22.5 Rear: 11R22.5 | | |

TRANSPORTATION

| | | |
|--------------------|--------|----------|
| Max. Driving Speed | 50 mph | 80 km/hr |
|--------------------|--------|----------|

STERLING CRANE

Dimensions

| 1500 Model | Retracted Length | Extended Length | Center of Rotation | Weight with Oil* |
|------------|-------------------|---------------------|--------------------|-------------------------|
| 15127 | 31 ft. (9.4 m) | 127 ft. (38.7 m) | 89 in (2.26 m) | 32,201 lb (14606 kg) |
| 15103 | 31 ft. (9.4 m) | 103 ft. (31.4 m) | 85 in (2.16 m) | 30,776 lb (13960 kg) |

*Weight includes all items including complete HO outriggers and SFO. Booms fully retracted.

